

FEELUX LIGHTING

MONORAIL SPOT HO

• Voltage : DC 24V
• Operating temperature : 32~113°F
• Lifetime : 50,000hrs / 70%
• Available color : 2700K, 3000K, 3500K, 4000K
• Color rendering : Ra > 85
• Lumens : 195lm
• Degree of protection : IP20
• Beam angle : 45°(STD), 25° and 60° available lens options
• Total energy consumption: 2.6W
• Maximum Connection: 96 Watts per power feed
• # of fixtures that can be connected on one power feed based on driver wattage
Specifications
Light Source Type: LED
Voltage: 24V DC
Operating Temperature: 32-113 °F (0-45 °C)
Available Color: 2700K, 3000K, 3500K, 4000K
Efficiency: 75lm/W
IP Rating: IP 20
Certifications List: UL, CE, CCC
Max Connection per Single Power Feed: 96W in one row (Single powerfeed)
See more information at www.feeluxlighting.com

ADDRESS:13000 NORTHWOODS PARKWAY SUITE 165PEACHTREE CORNERS, GA 30071
CALL:
678 668 7005
WEBSITE:
WWW.FEELUXLIGHTING.COM

Visual Market Retail (VMR) is a division of wests Design Consultants Limited Copyright © 2025 Visual Market Retail